


# DCSM Standing Seam Metal Roofing



Double Striated



Multi Striated

**DCSM** offers a variety of mechanical and snap-lock profiles including radius, domes, convex and concave as well as many architectural structures. Our **double and multi striated profiles help** prevent "oil canning" and adds texture to the design. Available in all DCSM standard colors.

|                                 |  |
|---------------------------------|--|
| <b>Application:</b>             | Architectural, Residential and Commercial.   |
| <b>Profiles:</b>                | Mechanical-lock, VS-150 snap-lock, VS-150 nail leg   |
| <b>Coverage:</b>                | 16" panel coverage, with a 1 1/2" seam height.   |
| <b>Minimum Slope:</b>           | Recommended slope 2/12 or greater.   |
| <b>Substrate:</b>               | Recommended substrate 1/2" - 5/8" plywood with a minimum 30 lb. underlayment.  |
| <b>Length:</b>                  | Panels are continuous lengths from eave to ridge.  |
| <b>Fastening System:</b>        | Concealed clip and fastener system. Recommended 2 screws per clip with a maximum clip spacing of 16" o/c.  |
| <b>Fasteners:</b>               | #10 x 1" flat head screws.   |
| <b>Materials:</b>               | Panels are fabricated from 26 gauge or 24 gauge Galvalume*.  |
| <b>Coatings &amp; Finishes:</b> | <b>26</b> gauge pre-painted Galvalume* panels are available in over 10 standard colors.<br><b>24</b> gauge pre-painted Galvalume* panels are available in over 30 standard colors and coated with a full-strength Kynar 500+ finish. |
| <b>Warranty:</b>                | 20, 25, and 35 year manufacturer warranties available.   |
| <b>Approvals &amp; Testing:</b> | Florida Building Code and Miami-Dade HVHZ product approvals.<br>TAS 125 (UL-580 uplift resistance test).<br>TAS 100-95 (wind driven rain test).<br>Class A Fire Rating (UL-790).<br>Quality Assurance Program.                       |

*At DCSM, all flashings and accessories are fabricated from the same coil stock as the panels*

\* All DCSM products are made from **Galvalume** not galvanized. Galvalume offers far superior corrosion resistance for the same price. Contact us for more product information.

## For More Information:



239.594.0530



info@dcsm.net



Visit us online!

DCSM, Inc. | 5700 Washington St | Naples, FL 34109 | P: 239.594.0530 | W: www.DCSM.net | E: info@dcsm.net

All accessories and flashings made from same color stock

This correspondence is intended for companies that have Established Business Relationship with D.C.S.M. Inc. If you have received this fax in error please call toll-free at 866-989-3276 to be removed from our database. Thank you.