

DCSM 5V Crimp



DCSM 5-V crimp is an exposed fastener, 5-rib panel available in many colors, Galvalume, aluminum and copper. DCSM also offers 5-V in all inclusive packages which includes all standard flashings and components in one per square price.

Application	Residential, Commercial, Industrial, and Agricultural.
Coverage	23.5" panel coverage, with a 5/8" seam height
Minimum Slope	Recommended slope 2/12 or greater
Substrate	Recommended substrate 1/2"-5/8" plywood with a minimum 30 lb. felt moisture barrier underlayment.
Length	Panels are continuous lengths from eave to ridge with no horizontal laps.
Fastening System	Exposed fastening system. Recommended that panels are fastened to substrate at center rib and inside rib of side lap, with a maximum spacing of 16" o/c.
Fasteners	1 1/2" self-sealing neoprene washer screws
Materials	Panels are fabricated from 26 gauge or 24 gauge Galvalume* Also available in Aluminum and Copper.
Coatings & Finishes	- 26 gauge pre-painted Galvalume* panels are available in over <u>10</u> standard colors. - 24 gauge pre-painted Galvalume* panels are available in over <u>30</u> standard colors and coated with a full-strength Kynar 500** finish.
Warranty	20, 25, and 35 year manufacturer warranties available
Approvals & Testing	- Florida Building Code and Miami-Dade HVHZ product approvals - TAS 125 (UL-580 uplift resistance test) - TAS 100-95 (wind driven rain test) - Class A Fire Rating (UL-790) - Quality Assurance Program

At DCSM, all flashings and accessories are fabricated from the same coil stock as the panels

* All DCSM products are made from **Galvalume** not galvanized. Galvalume offers far superior corrosion resistance for the same price. Contact us for more product information.

For More Information:



239.594.0530



info@dcsm.net



Visit us online!